



# UT380 SERIES

## Luminometers

### UT381/UT382



UT381



UT382

**NEW**

#### SPECIFICATIONS

Basic Functions		Range	Best Accuracy	
			UT381	UT382
Illuminance Measurement	LUX	20 Lux	$\pm(3\%+20)$	$\pm(3\%+20)$
		200 Lux	$\pm(3\%+8)$	$\pm(3\%+8)$
		2000 Lux	$\pm(3\%+8)$	$\pm(3\%+8)$
		20000 Lux	$\pm(3\%+8)$	$\pm(3\%+8)$
Illuminance Measurement	CD	2CD		
		20CD		
		200CD		
		2000CD		

#### Special Functions

Special Functions		UT381	UT382
Data Hold	Display "HOLD"	✓	✓
Illuminance Measurement	Display "Lux/CD"	✓	✓
Max / Min Mode	Display "max" or "min"	✓	✓
Sleep Mode	Around 10 Minutes	✓	✓
Low Battery Display	Around <7.1V	✓	✓
Data Logging		✓	✓
Auto Ranging		✓	✓
Real Time Clock		✓	✓
Working Temperature	0°C~40°C(32°F ~ 104°F)	✓	✓
Deposited Temperature	-10°C~55°C(14°F~122°F)	✓	✓
Relative Humidity	≤75%	✓	✓
USB			✓

#### GENERAL CHARACTERISTICS

Power	9V Alkaline Battery × 1
LCD Size	22.5 × 32.5mm
Product Colour	Red and Grey
Product Net Weight	185g
Product Size	195 × 45 × 26mm
Standard Accessories	USB Interface Cable, CD( <b>UT382 Only</b> ), English Manual, Carrying Bag, Battery
Standard Individual Packing	Blister
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	650 × 560 × 300 mm (0.11CBM Per Standard Carton)
Standard Carton Gross Weight	15kg